

Series 600 SD/SA

MODEL: AS-606-SD/SA

Stand Alone Photo Electric Smoke Detector with base, inbuilt battery backup, inbuilt buzzer with sound output 85 dB upto 3 Meters, front smoke chamber.

Features :

1. Long lasting battery upto 18 months
2. Test button to check battery and detector condition
3. Removable 9V battery
4. Easy to mounting
5. High quality ABS enclosen
6. High sensitive to smoke and automatic reset
7. Option for fire sound and beep sound

Technical Specification :

Power Source	: 9V Battery (included)
Audio Alarm	: 85dB at 10ft (3meters)
Temperature Range	: 40°F to 100°
Humidity Range	: 5%-95% relative humidity (RH)
Sensor	: Photoelectric
Size	: 105mm in diameter x 59mm depth
Weight	: 135g
Interconnects	: No
LED	: Red, Normal operation
Warranty	: 1 years limited (without Battery)



Notice:

1. The detector can not be installed under worse environment e.g. Coldest and dusty. Do not remove the dust proof cover until use the detector.
2. Make sure that there is no block within 0.5m form detector .
3. Keep the distance between detector and wall more than 0.5m.
4. Detector should be install Horizontally. If need, to be installed slantingly please keep the angle less than 45 degrees.
5. Make sure the distance between detectors be less than 3.5m. And the distance between detector and corner must be less than half of the one between detectors.
6. Detectors base be installed solid. Wire connection must be reliable.
7. Recommendations should be carried out every six months a simulated fire test, the detectors are working properly.
8. For various reason like change in environmental condition, electric disturbance and tampering, the product may not perform as expected. The user is advised to take all necessary precautions for his/her safety and protection of his/her property.